


1. Galvanized steel top hinge assembly. Consists of ; top pin rollers, roller pin, & roller pin clip.
2. Galvanized steel top clamp
3. Nuts & bolts to secure bearing plate to top clamp.
4. Galvanized steel bearing plate.
5. Anodized aluminum hinge covers.
6. Hinge cover screws.
7. Galvanized steel bottom door clamp.
8. Galvanized steel bottom hinge assembly (Bottom pin).
9. .032 anodized aluminum satin finish upper panels.
10. 9"W X 14"H clear safety acrylic

11. Black rubber window molding.
12. 48" high base plates 18 ga. galvanized steel both sides.
13. 3/4" thick plywood core.
14. Galvanized steel trim.


**MODEL SS-2**

12. 48" high baseplates, 18 ga. stainless steel on one side, 18 ga. galvanized steel on the other side.
- Required: Yes: \_\_\_ No: \_\_\_


**A** Spring bumpers up to 48". Material 3/16" Surlyn \_\_\_ or 5/16" thick H.D.P. \_\_\_ Spring bumper to be \_\_\_" high.




**C** Raised galvanized steel floor mounted jamb Guards. 9" high \_\_\_ or 18" \_\_\_ high.




**E** Chain locking collar.




**B** Custom window design



**D** 1/2" thick x 4" high HDP cart guard.



**F** 6"W x 12f1H stainless steel hand push plates.




STEEL JAMB  
1/4" TH. x 4" FACE  
RECOMMENDED

CUSTOMER \_\_\_\_\_

PROJECT \_\_\_\_\_

QUANTITY \_\_\_\_\_

APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**SOLID WOOD CORE DOOR**

SERIES 1000      DWG. SS-1-1-93